

Hydrogen Peroxide - B-Cap Antimicrobial Agent

B-Cap 70 EPA reg. No. 72372-3

B-Cap 50 EPA reg. No. 72372-2

B-Cap 35 EPA reg. No. 72372-1

CAS NO 7722-84-1

Introduction

B-Cap 35 and B-Cap 50 Antimicrobial Agents are EPA registered and may be used for biofouling control in cooling and process water systems, as a paper mill biocide, and for general slime control. B-Cap 50 and B-Cap 70 are for manufacturing and can be used in any FIFRA registered product formulation using H₂O₂ as an active ingredient.

Specifications

	<u>35%</u>	<u>50%</u>	<u>70%</u>
H ₂ O ₂ content, % by weight			
Product diluted at FMC sites	35.0-35.8	50.0-50.8	70.0-70.8
Stability, 24 hours @ 100° C	≥96.0%	≥96.0%	≥96.0%

Typical Properties

	<u>35%</u>	<u>50%</u>	<u>70%</u>
Loss in % assay, 1 yr, 25° C	<2.0	<2.0	<1.4
Apparent pH	2.0-3.0	1.0-2.0	0-1.0
Active oxygen content, %	16.5	23.5	32.9
Specific gravity (20° C)	1.13	1.20	1.29
Lbs/gal (kg/M ³ or g/L) @ 20° C	9.4 (1126)	10.0 (1198)	10.8 (1294)
Boiling point, ° C (° F)	108 (226)	114 (237)	126 (259)
Freezing point, ° C (° F)	-33 (-27)	-52 (-62)	-40 (-40)

Standard Containers

Polyethylene drums: 15 gallon (56.8 liter), 30 gallon (113.6 liter), 55 gallon (208.2 liter), and Polyethylene totes 200-300 gallons (757-1135 liters).

Shipment in tank trucks and tank cars is available.

Hydrogen peroxide above 8% concentration is classified as an "Oxidizer" by the Department of Transportation and all containers must carry the yellow DOT label or placard.

NOTICE

The information contained herein is, to our knowledge, true, and accurate. However, we make no warranty or representation, expressed or implied, except that FMC products discussed herein conform to the chemical description shown on their labels. Nothing contained herein shall be construed as permission or recommendation to infringe any patent. No agent, representative or employee of this company is authorized to vary any of the terms of this notice.